

MAXI 24



Electric and automatic steam boiler, power between 6 and 22 kW, steam pressure from 1 to 7 bar

Electric and automatic steam boiler, available from 6 to 22 kW. Water feed can be connected directly to the water mains or to a condensate tank. Regulation of the working steam pressure is adjustable between 1 and 7 bar.

Maxi 24 is available with a single group of heaters (three elements) or with two independent sets of heaters (six elements). The boiler shell is manufactured in accordance to the current PED regulations.

Technical Specifications	MAXI 24
Voltage	230V/400V/3/50-60 Hz
Steam working pressure	0,3 ÷ 7 bar
Boiler capacity	24.9 l
Pump motor	0.55 kW
Steam tap height	620 mm
Condensate recovery	380 mm
Overall dimensions	580x660x730 mm
Net weight	85 Kg
Gross weight (crate)	111 Kg
Packing dimensions	880x730x1050 mm

Options

- Stainless steel condensate tank
- Double sets of heaters.
- Boiler body in stainless steel AISI 304
- All components in contact with water in stainless steel AISI 304

Available electric powers and steam output

MAXI 24 (one set of heaters)		MAXI 24 (two sets of heaters)	
kW	Kg/h	kW	Kg/h
6	8,10	4+4	11
7	9,5	6+6	16
10	13,5	7+7	18,5
12	16	8+8	21
15	20	10+10	26,5
18	24,5	15+7	29,7

www.vyvijaceparry.sk

+421 905 162 119